

S.O COMPRESSO SHC SYNTHETIC COMPRESSOR OILS

DESCRIPTION

S.O COMPRESSO SHC are premium synthetic compressor oils blended with hydroisomerised base oils and selected additives. These oils with natural high viscosity index possess excellent high and low temperature performance, exhibit superior anti-oxidation, anti-wear, anti-corrosion and demulsification properties. They meet the specification requirement of DIN 51506 VDL.

CHARACTERISTICS

- Superior anti-oxidation and anti-rust properties
- Excellent thermal stability
- Excellent chemical stability
- Effectively resist sludging deposit
- Excellent demulsifiability
- Resistance to foaming
- Good filterability and air release property
- Long oil drain interval

APPLICATION

SO COMPRESSO SHC are suitable for use in rotary screw and reciprocating air compressors with temperature up to 230C.

TYPICAL SPECIFICATION

SAE GRADE		46
Kinematic Viscosity, cSt		
@ 40oC	ASTM D445	46
@ 100oC	ASTM D445	7.6
Viscosity Index	ASTM D2270	130
Flash Point (COC), oC	ASTM D92	245
Pour Point, oC	ASTM D97	-15

Version 03/21



AP Oil Pte. Ltd.
A member of AP Oil Int'l Ltd

18 Pioneer Sector 1, Jurong, Singapore 628428
tel 65 6861 5503 fax 65 6861 9162

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.