

S.O X-SUPER DIESELUBE CI-4

HIGH SPEED SEVERE DUTY DIESEL ENGINE OIL

DESCRIPTION

S.O X-SUPER DIESELUBE CI-4 are super premium quality diesel engine oils formulated for severe duty diesel engines with EGR emission systems including Euro IV engines. The oils possess improved high temperature oxidation stability and corrosion protection, enhanced dispersancy and soot controlling capability under high temperatures. **S.O X-SUPER DIESELUBE CI-4** meet specifications of API CI-4, CH-4, CG-4, SL, CF-2, MBp228.3, MAN M3275, Cat ECF-1-a, MTU Type II, Volvo VDS-2/3, Cummins 20071/76/78, 20072/77, Mack EO-M(Plus), ACEA A3/B3/B4, ACEA E5/E7 and global DHD-1.

CHARACTERISTICS

- Excellent dispersancy and detergency properties
- Outstanding oxidation stability
- Effective control over high temperature piston deposits
- Protect engine against wear, corrosion
- Keep engine clean
- Lower exhaust emission
- Prolong engine life

APPLICATIONS

S.O X-SUPER DIESELUBE CI-4 are recommended for use in high speed four stroke diesel engines with EGR emission treatment systems. It is suitable for all kinds of European diesel engines both on-highway and off-highway, running on high and low sulphur diesels. These oils can also be used for gasoline engines requiring API SL grade oils.

TYPICAL SPECIFICATION

SAE GRADE		10W/30
Kinematic Viscosity, cSt		
@ 40°C	ASTM D445	79
@ 100°C	ASTM D445	11.7
Viscosity Index	ASTM D2270	140
Flash Point (COC), °C	ASTM D92	210
Pour Point, °C	ASTM D97	-36
TBN, mgKOH/gm	ASTM D2896	12

Version 03/21



AP Oil Pte. Ltd.
A member of AP Oil Int'l Ltd

18 Pioneer Sector 1, Jurong, Singapore 628428
tel 65 6861 5503 fax 65 6861 9162

Due to continuous research and development, the above typical data is subject to change without notice. The information should not be regarded as legally binding assurance of any properties or suitability for any particular application.